

Farwest Paint Manufacturing Co.
 4522 South 133rd Street
 Tukwila, Washington, 98168
<http://www.farwestpaintmfg.com>
 Sections I-IV

Material Safety Data Sheet
For Coatings and Related Materials
Prep: Dec. 1991 Update: Mar. 2000

Manufactured For
 Parker Paint Co Inc
 3003 South Tacoma Way
 Tacoma, WA 98409

24 Hour Emergency Assistance

Emergency (Chemtrec) (800) 424-9300
 Information (Farwest) (206) 244-8844

Section I - Product Identification

Product Number: 2690 White, 2691 Yellow, 2692 Red
Product Name: Lead Free Latex Traffic Line Paint
Color: White & Tints

Product Class: Pigmented Acrylic Latex

Hazardous Material: Yes: No: XX

EPA Registration Number (if applicable): N/A

<i>Hazard Rating</i>		<i>This Product</i>
0	Lowest	
1		
2		
3		
4	Extreme	

Section II - Hazardous Ingredients

<i>Ingredient</i>	<i>CAS Number</i>	<i>Percent (By Weight)</i>	<i>Occupational Exposure</i>	
			<i>TLV (ACGIH)</i>	<i>PEL (OSHA)</i>
Ethylene Glycol	107-21-1	1.21%	50ppm	50ppm
Texanol (Ester Alcohol)	25265-77-4	1.05%	100ppm	100ppm
Methanol	67-56-1	<2.00%	200ppm	200ppm

"Pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, this product contains or may contain a toxic chemical in a quantity subject to the reporting requirements under Section 313"

Section III - Physical Data

Boiling Range: 212 F.	Weight/Gallon: 14.0 lbs.	Vapor Pressure: 23.8mmHg@20C
Vapor Density:	Heavier than Air: XX	Lighter than Air:
Evaporation Rate:	Faster than Ether:	Slower than Ether: XX
Percent Volatile by Volume: 40% pH: 9.0		Solubility in Water: Infinite
VOC: 92 Grams/Liter (Less Water)	Viscosity: 80-90 KU	Reactivity in Water: None
Melting Point: Unknown	Freezing Point: 32 F.	Decomposition Temp: Unknown
Autoignition Temp: Unknown	Corrosion Rate: Unknown	Specific Gravity: 1.681
Appearance & Odor: White (or tinted) liquid, slight odor.		

Section IV - Fire and Explosion Hazard Data

Flammability Classification:	OSHA: Nonflammable	Flash Point: N/A. TCC
	Class: Not Restricted	LEL: N/A UEL: N/A
	DOT: Nonflammable-Paint	

U.S. Postal Regulations: Nonflammable, Nonhazardous, OK to ship by mail.

Extinguishing Media: Foam, Dry Chemical, Water or Water Fog.

Special Firefighting Procedures: Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus. Evacuate area of unprotected personnel. Wear protective clothing.

Unusual Fire and Explosion Hazards: Will not burn; closed containers may burst if exposed to extreme heat. Water may be used to cool and protect exposed containers.

1952WHITEandTINTS ([latex](#))