

# MATERIAL SAFETY DATA SHEET

MSDS #QS18A

ABBREVIATIONS: NA = NOT APPLICABLE  
ND = NOT DETERMINED  
NE = NOT ESTABLISHED

HEALTH = 2  
FLAMMABILITY = 3  
REACTIVITY = 1  
PERSONAL PROTECTION = G

## SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT NAME: QUIK STRIPE AEROSOL PAINT, ALL COLORS

PRODUCT TYPE: AEROSOL

PIONEER MANUFACTURING COMPANY  
4529 INDUSTRIAL PARKWAY  
CLEVELAND, OHIO 44135  
TELEPHONE: (216) 671-5500

EMERGENCY TELEPHONE (800) 535-5053  
INFOTRAC

DATE PREPARED: 12/18/09

PREPARED BY: GSS

D.O.T. SHIPPING NAME ORMD - CONSUMER COMMODITY

## SECTION 2 - HAZARDOUS INGREDIENTS

CHEMICAL NAME:	CAS NO.	OSHA PEL	ACGIH TLV	% WT
ALIPHATIC HYDROCARBON	64742-89-8	500 ppm	100 ppm	20
ACETONE	67-64-1	750 ppm	750 ppm	10
MINERAL SPIRITS	8052-41-3	100 ppm	100 ppm	
CALCIUM CARBONATE	1317-65-3	NE	10 mg/M3	20
TOLUENE *	108-88-3	100 ppm	50 ppm	5
PROPANE/BUTANE BLEND	68476-86-8	ND	ND	20
XYLENE*	1330-20-7	100 ppm	Not known	<1

\* SUBJECT TO REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313, 40 CFR 372

## SECTION 3 - PHYSICAL DATA

BOILING POINT (° F)	NA.	SPECIFIC GRAVITY: 1.1-1.2 (PAINT)
VAPOR PRESSURE:	NE	MELTING POINT: NA
VAPOR DENSITY:	HEAVIER THAN AIR	EVAPORATION RATE (BUAC=1): SLOWER THAN BUAC
SOLUBILITY IN WATER:	INSOLUBLE	pH: NA
APPEARANCE/ODOR:	COLORED LIQUID, MILD SOLVENT ODOR	

## SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): -10 F T.O.C.

FLAMMABILITY LIMITS: LEL 1.1 UEL 12.8

EXTINGUISHING MEDIA: WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL.

SPECIAL FIRE FIGHTING PROCEDURES: EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CANS.

UNUSUAL FIRE FIGHTING AND EXPLOSION HAZARDS: WATER STREAMS WOULD SPREAD FIRE. STATIC ELECTRICITY COULD CAUSE IGNITION.

FOR CHEMICAL EMERGENCY  
Call INFOTRAC  
1-800-535-5053  
24 hours per day, 7 days per week

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



PRODUCT NAME: QUIK STRIPE AEROSOL PAINT ALL COLORS

MSDS #QS18A

---

#### SECTION 5 - REACTIVITY DATA

---

STABILITY: STABLE                      CONDITIONS TO AVOID: AVOID EXPOSURE TO HIGH HEAT.  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
INCOMPATIBILITY:  
HAZARDOUS DECOMPOSITION BYPRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, SMOKE.

---

#### SECTION 6 - HEALTH HAZARD DATA

---

ROUTES OF ENTRY: INHALATION? Y      SKIN? Y                      INGESTION? Y  
HEALTH HAZARDS (ACUTE AND CHRONIC): INHALATION MAY CAUSE DIZZINESS, DROWSINESS AND  
HEADACHE. INGESTION MAY CAUSE NAUSEA AND VOMITING. HIGH LEVEL EXPOSURE MAY CAUSE DAMAGE  
TO KIDNEYS AND LIVER. IRRITATING TO EYES AND SKIN.  
CARCINOGENICITY:                      NTP? N      IARC MONOGRAPHS? N      OSHA REGULATED? N

SIGNS AND SYMPTOMS OF EXPOSURE: SEE HEALTH HAZARDS ABOVE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES: EYE CONTACT: FLUSH WITH WATER FOR AT LEAST 15 MINUTES  
WHILE HOLDING EYE LIDS OPEN, SEE A PHYSICIAN. SKIN CONTACT: WASH WITH SOAP AND WATER OR  
WATERLESS HAND CLEANER AND WASH CLOTHING. IF IRRITATION PERSISTS, SEE A DOCTOR. INHALATION:  
REMOVE PERSON TO FRESH AIR. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION AS REQUIRED.  
INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

---

#### SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

---

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR LEAKED: WEAR APPROPRIATE PROTECTIVE GEAR.  
ELIMINATE SOURCES OF IGNITION. CONTAIN SPILL. REMOVE FREE LIQUID TO A SECURE CONTAINER. USE  
INERT ABSORBENT TO PICK UP RESIDUE. WASH AREA WITH DETERGENT AND WATER.  
WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL  
REGULATIONS.

PRECAUTIONS TO BE TAKEN IN STORAGE AND HANDLING: DO NOT STORE NEAR HEAT, SPARKS OR OPEN  
FLAME. DO NOT STORE IN DIRECT SUNLIGHT. KEEP CONTAINER CLOSED WHEN NOT IN USE.  
OTHER PRECAUTIONS: NONE KNOWN.

---

#### SECTION 8 - CONTROL MEASURES

---

RESPIRATORY PROTECTION: NIOSH APPROVED RESPIRATOR TO CONTROL AIRBORNE TLV.

VENTILATION:                      LOCAL EXHAUST TO MAINTAIN TLV      SPECIAL  
   MECHANICAL TO MAINTAIN TLV      OTHER

PROTECTIVE GLOVES: NEOPRENE RUBBER                      EYE PROTECTION: CHEMICAL GOGGLES  
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: LONG PANTS AND SLEEVES TO PREVENT SKIN CONTACT.

WORK/HYGENIC PRACTICES: WASH AFTER USING AND BEFORE EATING OR SMOKING.