

Fire Hazard **National Fire Hazardous Material** 1 **Protection Information System Fire Hazard** 2 Health Reactivity **Association** (HMIS) Reactivity 0 (NFPA)

Specific Hazard

Emergency Clear Liquid. See Section 9. Protective None required. WARNING: Aspiration into the lungs may cause Clothing Overview

chemical pneumonitis. COMBUSTIBLE.

| Section 1. Chemical Product and Company Identification | | | | |
|---|------------------------------------|---|---------------------------------|--|
| Product Name | PAINT, OIL & GREASE SPOTTER LIQUID | | Code | 3861 |
| Product Use | | | PMS# | 433202 |
| MSDS# | 126058001 | | Validation Date | 6/9/2004 |
| U.S. Headquarters | | Canadian Headquarters | Print Date | 6/9/2004 |
| JohnsonDiversey, Inc. 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.johnsondiversey.com | | JohnsonDiversey - Canada, Inc. 2401 Bristol Circle Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131 | Supersedes In Case of Emergency | No Previous Validation (800) 851-7145 |

| Section 2. Composition and Information on Ingredients | | | | |
|---|--------------------------|-------------|---|---|
| Ingredients | CAS# | % by Weight | Exposure Limits | LC50/LD50 |
| Alcohols, C12-14, ethoxylated Naphtha | 68439-50-9 64742-95-6 | | Not available. Not available. | Not available. ORAL (LD50): Acute: 8400 mg/kg [Rat]. >2150 mg/kg [quail]. |
| 1,2,4-Trimethylbenzene | 95-63-6 | 1-5 | OSHA (United States). TWA: 125 mg/m³ ACGIH (United States). TWA: 123 mg/m³ | ORAL (LD50): Acute: 5000 mg/kg [Rat]. VAPOR (LC50): Acute: 18000 mg/m³ 4 hour(s) [Rat]. |
| Isoparaffinic Hydrocarbon Solvent | 25551-13-7 | 1-5 | OSHA (United States). TWA: 125 mg/m³ ACGIH (United States). TWA: 123 mg/m³ ACGIH TLV (United States, 2003). Notes: TWA: 123 mg/m³ 8 hour(s). TWA: 25 ppm 8 hour(s) | ORAL (LD50): Acute: 8970 mg/kg [Rat]. |
| Xylene | 1330-20-7 | 1-5 | OSHA (United States). TWA: 435 mg/m³ STEL: 655 mg/m³ ACGIH (United States). TWA: 434 mg/m³ STEL: 651 mg/m³ ACGIH TLV (United States, 2003). Notes: 1996 Adoption Identifies substances identified in the BEI documetations for | ORAL (LD50): Acute: 4300 mg/kg [Rat]. 2119 mg/kg [Mouse]. 4300 mg/kg [Mammal]. DERMAL (LD50): Acute: >1700 mg/kg [Rabbit]. VAPOR (LC50): Acute: 5000 ppm 4 hour(s) [Rat]. |

| Johnson wax PROFESSIONAL PA | AINT, OIL & | GREASE S | POTTER LIQUID | Material Safety Data Sheet |
|--|-------------|----------|--|--|
| Dipropylene Glycol Methyl Ether | 34590-94-8 | 10-30 | Methemoglobin inducers (for which methemoglobin is the principle toxicity) and organophosphorous cholinesterase inhibitors are part of this notation. Refers to Appendix A Carc STEL: 651 mg/m³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 434 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s). OSHA PEL (United States, 1993). Notes: TWA: 435 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s) OSHA (United States). Skin TWA: 600 mg/m³ 8 hour(s). STEL: 900 mg/m³ ACGIH (United States). Skin TWA: 606 mg/m³ STEL: 909 mg/m³ ACGIH TLV (United States, 2003). Skin Notes: STEL: 909 mg/m³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 606 mg/m³ 8 hour(s). TWA: 606 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s). OSHA PEL (United States, 1993). Skin Notes: TWA: 600 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s). TWA: 100 ppm 8 hour(s). TWA: 100 ppm 8 hour(s). | ORAL (LD50): Acute: 7500 mg/kg [Dog]. DERMAL (LD50): Acute: 9480 mg/kg [Rabbit]. |
| Mineral Spirits | 64742-88-7 | 60-100 | Not available. | Not available. |

| Section 3. Hazards Identification | | |
|--|--|--|
| Routes of Entry | Inhalation. Skin contact. Eye contact. | |
| Potential Acute Health Effe | ects | |
| Eyes | None known. | |
| Skin | Prolonged or repeated contact may dry skin and cause irritation. | |
| Inhalation | May cause: nausea/vomiting, dizziness/vertigo, central nervous system depression. Repeated or prolonged inhalation of vapors may lead to chronic respiratory irritation. | |
| Ingestion | Aspiration during ingestion or vomiting can result in serious lung damage | |
| Medical Conditions Aggravated by Overexposure: | Persons with pre-existing skin disorders may be more susceptable to irritating effects. | |
| See Toxicological Information (section 11) | | |



| Section 4. First Aid Measures | | |
|-------------------------------|---|--|
| Eye Contact | Rinse with plenty of running water. | |
| Skin Contact | Rinse with plenty of running water. | |
| Inhalation | If breathing is difficult: Remove to fresh air. Get medical attention. | |
| Ingestion | Do not induce vomiting! Immediately drink 1-2 glasses of water or milk. Never give anything by mouth to an unconscious person. Get medical attention immediately. | |

| Section 5. Fire Fighting Measures | | |
|---|--|--|
| Flammability of the | COMBUSTIBLE. | |
| Product | | |
| Flash Points | CLOSED CUP: 41°C (105.8°F). | |
| Products of Combustion | None known. | |
| Fire Fighting Media and Instructions | Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide. | |
| Protective Clothing (Fire) | Put on appropriate personal protective equipment (see Section 8). | |
| Special Remarks on Fire and Explosion Hazards | Material may burn in heat of fire. Liquid will float and may reignite on surface of water. | |

| Section 6. Accidental Release Measures | | |
|--|--|--|
| Personal Precautions | ersonal Precautions Put on appropriate personal protective equipment (see Section 8). | |
| Environmental Precautions and Clean-up Methods | Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods. | |

| Section 7. Ha | andling and Storage |
|---------------|---|
| Handling | Do not taste or swallow. Avoid breathing vapors or spray mists. Use appropriate hygiene measures when handling product. Use only in well-ventilated areas. Aspiration into the lungs may cause chemical pneumontis. FOR COMMERCIAL AND INDUSTRIAL USE ONLY. |
| Storage | Store in a dry, cool and well-ventilated area. Protect from freezing. Keep away from heat, sparks and flame. KEEP OUT OF REACH OF CHILDREN. |

| Section 8. Exposure Controls/Personal Protection | | |
|--|---|--|
| Engineering Controls | Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained. | |
| Personal Protection Ey | es No special requirements under normal use conditions. | |
| Han | ds No special requirements under normal use conditions. For prolonged or repeated contact with skin: Neoprene gloves. | |
| Respirato | ry If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. | |
| Fe | pet No special requirements under normal use conditions. | |
| Во | dy No special protective clothing is required. | |



Section 9. Physical and Chemical Properties Liquid.

Physical State and

Appearance

Odor Fruity. Hydrocarbon.

Color Clear 0.82 Specific Gravity Solubility in water Negligible.

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Conditions of Instability

Excessive heat.

Incompatibility with Various Substances

Reactive with oxidizing agents.

Hazardous Decomposition When exposed to fire: Produces normal products of combustion.

Products

Hazardous Polymerization Will not occur.

Section 11. Toxicological Information

ORAL (LD50) Greater than 5000 mg/kg (rat). Acute toxicity

Effects of Chronic

Exposure

None known.

Other Toxic Effects Not available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information Burn in an appropriate incinerator or offer to a licensed hazardous waste disposal contractor.

Undiluted product is regulated under environmental and transportation laws as an ignitable

waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Proper Shipping Name Please refer to the Bill of Lading/receiving documents for up to date shipping information.

TDG Classification

TDG Proper Shipping Name Please refer to the Bill of Lading/receiving documents for up to date shipping information.

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal SARA 302/304/311/312 hazardous chemicals: Dipropylene Glycol Methyl Ether,

1,2,4-Trimethylbenzene, Isoparaffinic Hydrocarbon Solvent

, Xylene

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Dipropylene

Glycol Methyl Ether, 1,2,4-Trimethylbenzene, Isoparaffinic Hydrocarbon Solvent

SARA 313 toxic chemical notification and release reporting: 1,2,4-Trimethylbenzene, Xylene

Clean Water Act (CWA) 311: Xylene

CERCLA: Hazardous substances.: Xylene



State New Jersey spill list: 1,2,4-Trimethylbenzene, Xylene

New Jersey: Dipropylene Glycol Methyl Ether, 1,2,4-Trimethylbenzene, Isoparaffinic Hydrocarbon Solvent

, Xylene

Massachusetts spill list: 1,2,4-Trimethylbenzene, Xylene

Massachusetts RTK: Dipropylene Glycol Methyl Ether, 1,2,4-Trimethylbenzene, Isoparaffinic

Hydrocarbon Solvent

, Xylene

Pennsylvania RTK: Dipropylene Glycol Methyl Ether, 1,2,4-Trimethylbenzene, Isoparaffinic

Hydrocarbon Solvent

, Xylene

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Not applicable.
Information

Canadian Regulations

Canadian NPRI Canadian NPRI: 1,2,4-Trimethylbenzene, Xylene.

WHMIS Classification CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

WHMIS Icon



Registered Product Not applicable.
Information

Chemical Inventory Status All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information

Other Special Not available.

Considerations

Version 1.01

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.